



Armchair with oak seat, back and frame available in finishes 306, 340 and 372. Wide version. Option of upholstered shell pad.

0.319 m³ 9 kg
 11.27 Ft 19.84 Lbs

	Backrest height	Seat height	Arm height	Width	Depth
Measures (mm)	800	445	655	620	570

- Frame** Solid oak legs and frame.
- Seat** Oak board. Option of upholstered shell pad covered with flexible flame retardant polyurethane foam with density between 25 kg/m³ and 40 kg/m³.
- Accessories** Polypropylene, felt or steel glides.
- Other materials** Zinc-nickel electrolyte screws. Galvanized screws. Polyvinyl acetate glue.

	Fabrics / Telas	Faux Leather / Ecopiel	
Upholstery	1 Soft-fiber Jacquard One Jacquard Three Citadel Sand Era Gravity Rivet Urban 2 Jacquard Two Solid & Stripes Loom One Circular One Pure Eco 3 Jacquard Four Medley Revive 1 Natte Main Line Flax Loom Two Mezzo	4 Jacquard 4 Special Nexus Field 2 Floyd Remix 3 Heritage Savane Loom Three Loom Four Cura Oceanic 5 Silk Synergy Step Step Melange Blazer Melange Nap Glow Chili Noma Re-wool	6 Go check Swing Chartres Loom Five Zori Patio 7 Canvas 2 Rime Select Clara 2 8 Capture Fiord 2 Tonus 4 Divina 3 Lopi Domino 9 Divina MD Divina Melange 3 Hallingdal 65 Steelcut Trio 3
		1 Valencia 2 Silvertex 3 Maglia 4 Dolce 8 Ultraleather Original Ultraleather Linen Ultraleather Pearlized 9 Brisa Original Brisa Distressed Brisa Fresco Brisa Mokume Ultraleather Cora Outdoor Ultraleather Pony Ultraleather Pro Ultraleather Promessa Ultraleather Promessa Outdoor Ultraleather Dwell Ultratech EcoTech	
		11 Ultraleather Reef Pro Ultraleather Volar Bio Ultratech Cove	
		10 Brisa Distressed Outdoor Ultraleather Distressed Outdoor Ultratech Helix Ultratech Wired	

Leather / Piel

- L1** High grade cow leather
Piel de vaca de 1ª categoría
- L3** Polished full grain leather
Plena flor pulida
- L6** Aniline leather batique-effect.
Scandinavian cattle.
Piel anilina efecto batique.
Ganado escandinavo.

Leather

RESISTANCE AND QUALITY UNE-EN 16139:2013
ISO 9001

FIREPROOF UNE-EN 1021-1:2006
B.S. 5852 Part 2 Crib V
UNI 9175 M-1
California Tech.Bulletin 117

SUSTAINABILITY ISO 14001
level® 2 certified to ANSI/BIFMA e3 Standard