



Hula 46. Barstool with upholstered shell and injection swivel central base, adjustable height and finished in different colors.

📦 0.17 m<sup>3</sup>
🏋️ 7 kg
 📏 6 Ft
 ⚖️ 15.43 Lbs
 📐

	Backrest height	Seat height	Width	Depth
<b>Measures (mm)</b>	760	680	460	510

**Frame** Injected aluminium swivel central base. Rotating system integrated into top of the structure. Injected aluminum plate fixes the base to the seat. Felt glides.

**Seat** Upholstered seat with flame retardant polyurethane flexible foam with a density between 25 kg/m<sup>3</sup> and 40 kg/m<sup>3</sup>

**Back** Upholstered back with flame retardant polyurethane flexible foam with a density between 25 kg/m<sup>3</sup> and 40 kg/m<sup>3</sup>

**Accessories** Felt glide.

**Other materials** Zinc-nickel electrolyte screws. Galvanized staples. Polyvinyl acetate glue.

**Leather / Piel**

**L1** High grade cow leather  
Piel de vaca de 1ª categoría

**L3** Polished full grain leather  
Plena flor pulida

**L6** Aniline leather batique-effect.  
Scandinavian cattle.  
Piel anilina efecto batique.  
Ganado escandinavo.

**Leather**



## Aluminum finish

### RESISTANCE AND QUALITY

UNE-EN 16139:2013

ISO 9001

### FIREPROOF

UNE-EN 1021-1:2006

B.S. 5852 Part 2 Crib V

California Tech.Bulletin 117

BKZ 5.2

### SUSTAINABILITY

FSC

ISO 14001

level® 2 certified to ANSI/BIFMA e3 Standard