



Hula 46. Barstool with upholstered shell and injection swivel central base finished in different colors.

📦 0.29 m<sup>3</sup>   👤 7.2 kg   📏 10.24 Ft   📏 15.87 Lbs   📏

	Backrest height	Seat height	Width	Depth
Measures (mm)	1,020	830	460	535

**Frame**

Injected aluminium swivel central base. Rotating system integrated into top of the structure. Injected aluminum plate fixes the base to the seat. Felt glides.

**Seat**

Upholstered seat with flame retardant polyurethane flexible foam with a density between 25 kg/m<sup>3</sup> and 40 kg/m<sup>3</sup>

**Back**

Upholstered back with flame retardant polyurethane flexible foam with a density between 25 kg/m<sup>3</sup> and 40 kg/m<sup>3</sup>

**Accessories**

Felt glide.

**Other materials**

Zinc-nickel electrolyte screws. Galvanized staples. Polyvinyl acetate glue.

**Leather / Piel**

**L1** High grade cow leather  
Piel de vaca de 1ª categoría

**L3** Polished full grain leather  
Plena flor pulida

**L6** Aniline leather batique-effect.  
Scandinavian cattle.  
Piel anilina efecto batique.  
Ganado escandinavo.

**Leather**



**Aluminum finish**

**RESISTANCE AND QUALITY**

UNE-EN 16139:2013  
ISO 9001

**FIREPROOF**

UNE-EN 1021-1:2006  
B.S. 5852 Part 2 Crib V  
California Tech.Bulletin 117  
BKZ 5.2

**SUSTAINABILITY**

FSC  
ISO 14001  
level® 2 certified to ANSI/BIFMA e3 Standard